HOW TO CARE FOR YOUR DECK ARMOR FLOORING

To keep your floor looking great and performing at its best, follow these simple care instructions:

✔ DO

- ✔ **Rinse with fresh water** using a hose or pressure washer with 2000 PSI or less.
- ✔ **Use Comet or Ajax with bleach** for deeper cleans. Apply with a soft-bristle brush or deck brush.
- ✔ It is safe to use **bleach with a 3:1 mix ratio.**
- ✔ **Clean up gas spills** promptly to avoid damage to the binder.

✕ DO NOT

- ✕ Do **not use liquid soap.** This will create soap scum build up.
- ✕ Do **not use a pressure washer tip** that's too close—keep nozzle at least 12" away.
- ✕ Do **not use steel wool** to clean.
- ✕ Do **not allow petroleum products** to stay on product. This will damage the binder.

WARRANTY INFORMATION & REGISTRATION

Warranty Coverage Period:

- **Boats:** Lifetime of ownership by the original purchaser
- **Docks:** 10 years from the date of installation

This warranty is non-transferable and applies only to the original purchaser, whether for boat or dock installations.

Service Location:

All warranty repairs will be performed at the original installation site. **Deck Armor Inc. is not responsible for any travel, transportation, or additional costs incurred.**

Warranty Covers:

Defects in materials or workmanship.

Warranty Does Not Cover:

- Damage caused by improper cleaning methods or use of non-recommended chemicals.
- Burns, cuts, gouges, or damage from excessive impact.
- Misuse or abuse, including improper pressure washing (e.g., holding the nozzle too close, using stronger than 2000 PSI).

217 S 78th Street, Tampa, FL 33619 • (813) 434-0395
Dave@deckarmor.com • www.deckarmor.com